


Pushdown Automata


PDA_s

Pushdown Automaton -- PDA


Input String




Stack




States















Initial Stack Symbol















The States
















A Possible Transition




input





stack





empty



A Bad Transition





Empty stack





HALT

The automaton **Halts** in state q_1
and **Rejects** the input string

A Bad Transition




Empty stack




HALT

The automaton **Halts** in state q_1
and **Rejects** the input string


No transition is allowed to be followed
When the stack is empty





Empty stack






A Good Transition





input



stack




Non-Determinism



These are allowed transitions in a
Non-deterministic PDA (NPDA)



NPDA: Non-Deterministic PDA

Example:




Execution Example: Time 0

Input





Stack

current state




Time 1

Input





Stack




Time 2

Input





Stack




Time 3

Input





Stack




Time 4

Input





Stack




Time 5

Input





Stack




Time 6

Input





Stack




Time 7

Input





Stack




Time 8

Input



Stack



A string is accepted if there is a computation such that:


All the input is consumed

AND

The last state is a final state

At the end of the computation,
we do not care about the stack contents


The input string $aaabbb$
is accepted by the NPDA:



In general,

$$L = \{a^n b^n : n \geq 0\}$$

is the language accepted by the NPDA:



Another NPDA example

NPDA M


$$L(M) = \{ ww^R \}$$

$a, \lambda \rightarrow a$

$a, a \rightarrow \lambda$



$b, \lambda \rightarrow b$

$b, b \rightarrow \lambda$



Execution Example: Time 0

Input




Stack

$a, \lambda \rightarrow a$

$a, a \rightarrow \lambda$



$b, \lambda \rightarrow b$

$b, b \rightarrow \lambda$



Time 1

Input




Stack

$a, \lambda \rightarrow a$

$b, \lambda \rightarrow b$



$a, a \rightarrow \lambda$

$b, b \rightarrow \lambda$



Time 2

Input




Stack

$a, \lambda \rightarrow a$

$b, \lambda \rightarrow b$


$a, a \rightarrow \lambda$

$b, b \rightarrow \lambda$




Time 3

Input



Guess the middle of string




Stack

$a, \lambda \rightarrow a$

$b, \lambda \rightarrow b$



$a, a \rightarrow \lambda$

$b, b \rightarrow \lambda$



Time 4

Input




Stack

$a, \lambda \rightarrow a$

$b, \lambda \rightarrow b$



$a, a \rightarrow \lambda$

$b, b \rightarrow \lambda$



Time 5

Input




Stack

$a, \lambda \rightarrow a$

$b, \lambda \rightarrow b$



$a, a \rightarrow \lambda$

$b, b \rightarrow \lambda$



Time 6

Input




Stack

$a, \lambda \rightarrow a$

$a, a \rightarrow \lambda$

$b, \lambda \rightarrow b$



$b, b \rightarrow \lambda$



Rejection Example:

Time 0

Input




Stack

$a, \lambda \rightarrow a$

$a, a \rightarrow \lambda$



$b, \lambda \rightarrow b$

$b, b \rightarrow \lambda$



Time 1

Input




Stack

$a, \lambda \rightarrow a$

$b, \lambda \rightarrow b$



$a, a \rightarrow \lambda$

$b, b \rightarrow \lambda$



Time 2

Input




Stack

$a, \lambda \rightarrow a$

$b, \lambda \rightarrow b$


$a, a \rightarrow \lambda$

$b, b \rightarrow \lambda$




Time 3

Input



Guess the middle of string




Stack

$a, \lambda \rightarrow a$

$b, \lambda \rightarrow b$



$a, a \rightarrow \lambda$

$b, b \rightarrow \lambda$



Time 4

Input




Stack

$a, \lambda \rightarrow a$

$b, \lambda \rightarrow b$

$a, a \rightarrow \lambda$


$b, b \rightarrow \lambda$




Time 5

Input

There is no possible transition.



Input is not consumed




Stack

$a, \lambda \rightarrow a$

$a, a \rightarrow \lambda$


$b, \lambda \rightarrow b$

$b, b \rightarrow \lambda$




Another computation on same string:

Input




Time 0



$a, \lambda \rightarrow a$
 $b, \lambda \rightarrow b$



$a, a \rightarrow \lambda$
 $b, b \rightarrow \lambda$

Stack



Time 1

Input




Stack

$a, \lambda \rightarrow a$

$b, \lambda \rightarrow b$



$a, a \rightarrow \lambda$

$b, b \rightarrow \lambda$



Time 2

Input




Stack

$a, \lambda \rightarrow a$

$b, \lambda \rightarrow b$



$a, a \rightarrow \lambda$

$b, b \rightarrow \lambda$



Time 3

Input




Stack

$a, \lambda \rightarrow a$

$b, \lambda \rightarrow b$



$a, a \rightarrow \lambda$

$b, b \rightarrow \lambda$



Time 4

Input




Stack

$a, \lambda \rightarrow a$

$b, \lambda \rightarrow b$


$a, a \rightarrow \lambda$

$b, b \rightarrow \lambda$




Time 5

Input



No final state is reached




Stack

$a, \lambda \rightarrow a$

$a, a \rightarrow \lambda$

$b, \lambda \rightarrow b$

$b, b \rightarrow \lambda$



There is no computation
that accepts string $abbb$


$$abbb \notin L(M)$$

$$a, \lambda \rightarrow a$$

$$a, a \rightarrow \lambda$$

$$b, \lambda \rightarrow b$$

$$b, b \rightarrow \lambda$$



A string is rejected if there is
no computation such that:

All the input is consumed

AND

The last state is a final state

At the end of the computation,
we do not care about the stack contents

In other words, a string is rejected if in every computation with this string:

The input cannot be consumed

OR

The input is consumed and the last state is not a final state

OR

The stack head moves below the bottom of the stack

Another NPDA example


NPDA M

$L(M) = \{w : w \in \{a,b\}^*, n_a \geq n_b \text{ for any prefix of } w\}$

$a, \lambda \rightarrow a$


$b, a \rightarrow \lambda$

$b, \$ \rightarrow \lambda$



Execution Example: Time 0


Input




$a, \lambda \rightarrow a$

$b, a \rightarrow \lambda$

$b, \$ \rightarrow \lambda$




Stack



Time 1



Input



$a, \lambda \rightarrow a$

$b, a \rightarrow \lambda$


$b, \$ \rightarrow \lambda$



Stack

Time 2



Input



$$a, \lambda \rightarrow a$$

$$b, a \rightarrow \lambda$$


$$b, \$ \rightarrow \lambda$$




Stack

Time 3


Input



$a, \lambda \rightarrow a$
 $b, a \rightarrow \lambda$
 $b, \$ \rightarrow \lambda$



Stack





accept


Rejection example:

Time 0

Input




Stack



Time 1



Input



$$a, \lambda \rightarrow a$$

$$b, a \rightarrow \lambda$$


$$b, \$ \rightarrow \lambda$$



Stack

Time 2



Input



$a, \lambda \rightarrow a$

$b, a \rightarrow \lambda$


$b, \$ \rightarrow \lambda$



Stack

Time 3



Input



$a, \lambda \rightarrow a$

$b, a \rightarrow \lambda$


$b, \$ \rightarrow \lambda$



Stack

Time 4


Input




$a, \lambda \rightarrow a$

$b, a \rightarrow \lambda$

$b, \$ \rightarrow \lambda$




Stack




Halt and Reject



Pushing Strings






Example:



input



stack



Another NPDA example


NPDA M

$$L(M) = \{w : n_a = n_b\}$$

$a, \$ \rightarrow 0\$$ $b, \$ \rightarrow 1\$$



$a, 0 \rightarrow 00$ $b, 1 \rightarrow 11$

$a, 1 \rightarrow \lambda$ $b, 0 \rightarrow \lambda$



Execution Example: Time 0


Input



Stack



- $a, \$ \rightarrow 0\$$ $b, \$ \rightarrow 1\$$
- $a, 0 \rightarrow 00$ $b, 1 \rightarrow 11$
- $a, 1 \rightarrow \lambda$ $b, 0 \rightarrow \lambda$

current state




Time 1

Input





Stack

$a, \$ \rightarrow 0\$$ $b, \$ \rightarrow 1\$$
 $a, 0 \rightarrow 00$ $b, 1 \rightarrow 11$
 $a, 1 \rightarrow \lambda$ $b, 0 \rightarrow \lambda$



Time 3

Input




$a, \$ \rightarrow 0\$$ $b, \$ \rightarrow 1\$$

$a, 0 \rightarrow 00$ $b, 1 \rightarrow 11$



$a, 1 \rightarrow \lambda$ $b, 0 \rightarrow \lambda$

Stack



Time 4

Input




Stack

$a, \$ \rightarrow 0\$$ $b, \$ \rightarrow 1\$$



$a, 0 \rightarrow 00$ $b, 1 \rightarrow 11$

$a, 1 \rightarrow \lambda$ $b, 0 \rightarrow \lambda$



Time 5

Input




Stack

$a, \$ \rightarrow 0\$$ $b, \$ \rightarrow 1\$$



$a, 0 \rightarrow 00$ $b, 1 \rightarrow 11$

$a, 1 \rightarrow \lambda$ $b, 0 \rightarrow \lambda$



Time 6

Input




Stack

$a, \$ \rightarrow 0\$$ $b, \$ \rightarrow 1\$$



$a, 0 \rightarrow 00$ $b, 1 \rightarrow 11$

$a, 1 \rightarrow \lambda$ $b, 0 \rightarrow \lambda$



Time 7

Input




Stack

$a, \$ \rightarrow 0\$$ $b, \$ \rightarrow 1\$$



$a, 0 \rightarrow 00$ $b, 1 \rightarrow 11$

$a, 1 \rightarrow \lambda$ $b, 0 \rightarrow \lambda$



Time 8

Input




Stack


$$a, \$ \rightarrow 0\$ \quad b, \$ \rightarrow 1\$$$

$$a, 0 \rightarrow 00 \quad b, 1 \rightarrow 11$$

$$a, 1 \rightarrow \lambda \quad b, 0 \rightarrow \lambda$$




Formalities for NPDAs



Transition function:

$$\delta(q_1, a, b) = \{(q_2, w)\}$$




Transition function:

$$\delta(q_1, a, b) = \{(q_2, w), (q_3, w)\}$$


Formal Definition

Non-Deterministic Pushdown Automaton NPDA

$$M = (Q, \Sigma, \Gamma, \delta, q_0, z, F)$$



Instantaneous Description





Example:

Instantaneous Description


$(q_1, bbb, aaa\$)$

Time 4:

Input



Stack





Example: Instantaneous Description


$(q_2, bb, aa\$)$

Time 5:

Input



Stack



We write:


$$(q_1, bbb, aaa\$) \succ (q_2, bb, aa\$)$$

Time 4

Time 5

A computation:

$(q_0, aaabbb, \$) \succ (q_1, aaabbb, \$) \succ$
 $(q_1, aabbb, a\$) \succ (q_1, abbb, aa\$) \succ (q_1, bbb, aaa\$) \succ$
 $(q_2, bb, aa\$) \succ (q_2, b, a\$) \succ (q_2, \lambda, \$) \succ (q_3, \lambda, \$)$



$$\begin{aligned}
& (q_0, aaabbb, \$) \succ (q_1, aaabbb, \$) \succ \\
& (q_1, aabbb, a\$) \succ (q_1, abbb, aa\$) \succ (q_1, bbb, aaa\$) \succ \\
& (q_2, bb, aa\$) \succ (q_2, b, a\$) \succ (q_2, \lambda, \$) \succ (q_3, \lambda, \$)
\end{aligned}$$

For convenience we write:

$$(q_0, aaabbb, \$) \overset{*}{\succ} (q_3, \lambda, \$)$$

Formal Definition

Language $L(M)$ of NPDA M :

$$L(M) = \{w : (q_0, w, s) \xrightarrow{*} (q_f, \lambda, s')\}$$

Initial state



Final state




Example:

$$(q_0, aaabbb, \$) \stackrel{*}{\succ} (q_3, \lambda, \$)$$



$$aaabbb \in L(M)$$

NPDA M :




$$(q_0, a^n b^n, \$) \stackrel{*}{\succ} (q_3, \lambda, \$)$$



$$a^n b^n \in L(M)$$

NPDA M :



Therefore: $L(M) = \{a^n b^n : n \geq 0\}$

NPDA M :

